



Dimension (W x D x H)
155 x 86 x 26 mm
Weight
368g
Operating Temperature
0~50°C

Performance:
(Down Stream /
Up Stream)

17a profile
300m -> 99/70Mbps
400m -> 99/60Mbps
600m -> 90/45Mbps
800m -> 50/28Mbps
1000m -> 40/12Mbps
1200m -> 20/7Mbps
1400m -> 20/4Mbps



30a profile
300m -> 100/100Mbps
400m -> 90/90Mbps

	DIP-1	DIP-2	DIP-3	DIP-4
	Mode	Channel	Profile	SNR
OFF	CO	Interleave	17A	9dB
ON (default)	CPE	Fast	30A	6dB

- Cost-effective VDSL2 CO/CPE bridge solution
- One box design, CO/CPE selectable via DIP Switch
- Defines profile 17a band plan for the long distance transmission of upstream and downstream signals
- Defines profile 30a band plan for the short distance transmission of upstream and downstream signals
- Complies with IEEE 802.3, IEEE 802.3u and IEEE 802.3x standards

JNT Systems AB/Commend Solutiont Örby Slottsväg 39, SE-125 71 Älvsjö, Sweden,
Phone +46 8 99 30 60, Fax + 46 8 99 55 80, e-mail jan@jnt.se , www.IP4U2.com
VAT no: SE556633677101,